

# V300 COMMERCIAL UPVC VINYL SERIES

## Casement | Project-Out | Fixed







Rating
Casement: CW50
Project-Out: CW50
Fixed: CW50



Design Pressure Casement: 50 Project-Out: up to 50 Fixed: 50	U-Value* Casement: .1741 Project-Out: .1742 Fixed: .1543
Air Infiltration Casement: <.30 Project-Out: <.30 Fixed: <.10	SHGC* Casement: .0951 Project-Out: .0951 Fixed: .1059
Water Resistance Casement: 7.5 Project-Out: 7.5 Fixed: 7.5	* CR* Casement: 32 - 77 Project-Out: 32 - 77 Fixed: 33 - 70
OITC <sup>X</sup> ))) Casement: 23 - 34  Project-Out/Fixed  Combination: 29	STC <sup>X</sup> ))) Casement: 29 - 42  Project-Out/Fixed  Combination: 35

\*-U-Value, SHGC and CR ranges are NFRC certified based on I.G. combinations incorporating some or all the following: Low-E glass, clear glass, argon gas and/or air fill, and grids

x-Ranges based on multiple I.G. combinations

### **FEATURES:**

- Architectural grade uPVC vinyl frame
- Fusion welded sash and frame corners
- ► Integral Nail Fin
- ▶ 1" Insulating Glass
- ► Clean exterior appearance
- Multi-Point locking system with heavy commercial 4-bar arms on operating models
- ▶ Wide or Narrow sightlines on fixed models
- White and Sandstone uPVC vinyl (exterior/ interior)
- Optional painted exterior (meets FGIA 615 finish)
- Textured laminate options for exterior and interior
- Use up to 8 floors with nail fin, up to 11 floors with receptor/subsill system
- Impact rated versions (V700 Series)




# V300 COMMERCIAL UPVC VINYL SERIES

#### Casement (CW50)


Test size = 36" x 78"

3.4058




#### Project-out (CW80)

Test size = 60" x 32"




### Fixed Narrow (CW50)

Test size = 78" x 78"



#### Fixed Wide (CW50)

Test size = 72" x 84"





QuakerCommercialWindows.com 1-800-347-0438 Commercial@quakerwindows.com

All ratings listed are NAFS certified.

