

Casement | Project-Out | Fixed





Frame Depth 3 1/4"



Rating
Casement: Up to CW90
Project-Out: Up to CW90
Fixed: Up to AW100



Design Pressure Casement: Up to 90 Project-Out: Up to 90 Fixed: Up to 100	U-Value* Casement: 0.30-0.39 Project-Out: 0.31-0.39 Fixed: 0.23-0.34
Air Infiltration Casement: <.30 Project-Out: <.30 Fixed: <.10	SHGC* Casement: 0.14-0.31 Project-Out: 0.14-0.31 Fixed: 0.16-0.37
Water Resistance Casement: Up to 15 Project-Out: Up to 15 Fixed: Up to 15	* CR* Casement: 43-58 Project-Out: 41-57 Fixed: 47-69
OITC#)))) Casement: 29-32 Project-Out: Fixed:	STC#)))) Casement: 34-37 Project-Out: Fixed:

*- U-Value and SHGC ranges are NFRC certified and based on I.G. combinations incorporating some or all the following: Low-E glass, clear glass, argon gas and/or air fill, and grids # - Ranges based on multiple I.G. combinations

All ratings listed are NAFS certified. Periodic re-certification testing is required thus data shown may vary slightly.


FEATURES:

- Historically-correct bevel frame
- ► Patented SolidCore® Technology
- ► Casement and Project-out operating models
- ► Matching Fixed model
- ► Architectural grade aluminum frame
- Thermally-broken frame and sash
- ► 2 5/16" narrow sitelines on operable units, and 1 1/2" on fixed
- With or without Integral Nailing Fin
- 1" insulating glass
- Exterior glazed
- Integral anchor leg
- Standard High-Performance 2604 Powder Paint Finish (an FGIA Specification). Optional upgrade to 2605 Finish (an FGIA Specification)
- 30+ "Quick-Pick" colors, with unlimited custom colors available.
- ► Impact rated versions (H470 Series): Project-Out model w/cam handle and Fixed model




H450 HISTORICAL ALUMINUM SERIES


Casement Roto




Casement Push-Out




Fixed




Project-Out Roto



Project-Out Push-Out



Floating Operator







QuakerCommercialWindows.com 1-800-347-0438 Commercial@quakerwindows.com