



## TimberVu W-Series Doors

The artistic fusing of an architectural aluminum exterior with the classic look and feel of a natural wood interior provides the ageless charm found only in TimberVu W-Series Doors.

Duality by design, the melding of these complimentary materials offer the chance to customize your living space and visually share the timeless comfort seen throughout the broad spectrum of contemporary architectural planning.



Unique to the market, Quaker's Patented SolidCore™ Thermal Barrier System integrates an Azo-Core high-density foam that acts as an insulator against the natural conductivity of heat and cold, allowing for superior energy performance and product integrity regardless of size or operational style.



Available in Swing or Sliding operational styles  
along with sidelites, transoms  
and multiple mulling configurations.

## TimberVu W-Series Swing Door Highlights, Performance and Operation

- Architectural Grade Aluminum Frame
  - 5-5/8" Frame Depth
  - 4-9/16" and 6-9/16" Jamb Depths
- Patented SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Available as Inswing (C200I) or Outswing (C200O)
- Adjustable Butt Hinges offer Multi-Directional Adjustment
- Standard, ADA, or No Sill Options
- Butt Joint Panels & Extruded Fin
- Wide and Narrow Panel Options
- Internal or Simulated Divided Light (SDLs) Grids Available
- Pine Interior
- High-Performance 2604 and 2605 Powder Finishes
- Custom Color Matching and Heat Reflective Paint Options

Series Options	
W200I	Inswing
W200O	Outswing

Swing Door Sizing (W200I / W200O)					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Single Panel	24"	48"	78"	120"	180"
Two Panel - French	48"	84"	78"	120"	216"
Sidelite - Narrow	15"	108"	15"	120"	191"
Sidelite - Fixed Panel Set	15"	108"	15"	120"	191"
Transom	12"	120"	12"	108"	191"

Swing Door Performance		
Operation / Style	Structural Rating	U-Value Range
Single Panel	R-50 / LC-50	0.26 - 0.31
Two Panel - French	R-50 / LC-50	0.26 - 0.31
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	

## TimberVu W-Series Sliding Door Highlights, Performance and Operation

- Architectural Grade Aluminum Frame
  - 5-5/8" Frame Depth
  - 4-9/16" and 6-9/16" Jamb Depths
- Patented SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Stainless Steel Quad Precision Bearing Roller System
- Butt Joint Panels & Extruded Fin
- Internal or Simulated Divided Light (SDLs) Grids Available
- Pine Interior
- High-Performance 2604 and 2605 Powder Finishes
- Custom Color Matching and Heat Reflective Paint Options

Series Options	
W200S	Sliding

Sliding Door Sizing (W200S)					
Operation	Width		Height		Max UI
	Min	Max	Min	Max	
Two Panel	60"	95"	78"	120"	264"
Four Panel	120"	193"	78"	120"	408"
Sidelite - Narrow	15"	108"	15"	120"	191"
Sidelite - Fixed Panel	15"	108"	15"	120"	191"
Transom	12"	120"	12"	108"	191"

Sliding Door Performance		
Operation / Style	Structural Rating	U-Value Range
Two Panel	R-50 / LC-50	0.24 - 0.29
Four Panel	R-50 / LC-50	0.24 - 0.29
SDL Depth (Max Profile Height)		
Exterior	7/16"	
Interior	9/16"	



**Quaker Window Products**  
 504 U.S. Hwy 63 South  
 Freeburg, MO 65035  
 (800) 347-0438  
[www.quakerresidentialwindows.com](http://www.quakerresidentialwindows.com)

Discover More Here :



RES-TV WD 0925