



## CityVu C-Series Doors

Combining the hard lines of architectural elegance with the softer tones of modern residential living, CityVu C-Series Doors by Quaker bring home the nuances of what contemporary living should be.

With both swing and sliding options, along with sidelites, transoms and multiple mulling configurations, this cross-functional family of doors have been designed to accentuate the seamless transition from inside to outside.



Unique to the market, Quaker's Patented SolidCore™ Thermal Barrier System integrates an Azo-Core high-density foam that acts as an insulator against the natural conductivity of heat and cold, allowing for superior energy performance and product integrity regardless of size or operational style.



## CityVu C-Series Swing Door Highlights, Performance and Operation

- Architectural Grade Aluminum Frame
  - 5-5/8" Frame Depth
  - 4-9/16" and 6-9/16" Jamb Depths
- Patented SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Available as an Inswing (C200I) or Outswing C200O
- Adjustable Butt Hinges offer Multi-Directional Adjustment
- Standard, ADA, or No Sill Options
- Butt Joint Corners & Extruded Fin
- Wide and Narrow Panel Options
- Internal or Simulated Divided Light (SDLs) Grids Available
- High-Performance 2604 and 2605 Powder Finishes
- Optional Exterior and Interior (Two-Tone) Color Finish Options
- Custom Color Matching and Heat Reflective Paint Options

### Series Options

C200I	Inswing
C200O	Outswing

### Swing Door Sizing (C200I / C200O)

Operational Style	Width		Height		Max UI
	Min	Max	Min	Max	
Single Panel	24"	48"	78"	120"	180"
Two Panel - French	48"	84"	78"	120"	216"
Sidelite- Narrow	15"	108"	15"	120"	191"
Sidelite - Fixed Panel Set	24"	108"	15"	120"	191"
Transom	12"	120"	12"	108"	191"

### Swing Door Performance

Operation / Style	Structural Rating	U-Value Range
Single Panel	R-50 / LC-50	0.27 - 0.31
Two Panel - French	R-50 / LC-50	0.27 - 0.31
<b>SDL Depth (Max Profile Height)</b>		
Exterior	7/16"	
Interior	9/16"	

## CityVu C-Series Sliding Door Highlights, Performance and Operation

- Architectural Grade Aluminum Frame
  - 5-5/8" Frame Depth
  - 4-9/16" and 6-9/16" Jamb Depths
- Patented SolidCore™ Thermal Barrier in Doors
- Corner Key Technology for Maximum Structural Performance
- Stainless Steel Quad Precision Bearing Roller System
- Butt Joint Panels & Extruded Fin
- Internal or Simulated Divided Light (SDLs) Grids Available
- High-Performance 2604 and 2605 Powder Finishes
- Optional Exterior and Interior (Two-Tone) Color Finish Options
- Custom Color Matching and Heat Reflective Paint Options

### Series Options

C200S	Sliding
-------	---------

### Sliding Door Sizing (C200S)

Operational Style	Width		Height		Max UI
	Min	Max	Min	Max	
Two Panel	60"	96"	78"	120"	264"
Four Panel	120"	193"	78"	120"	408"
Sidelite - Narrow	15"	108"	15"	120"	191"
Sidelite - Fixed Panel Set	24"	108"	15"	120"	191"
Transom	12"	120"	12"	108"	191"

### Sliding Door Performance

Operation / Style	Structural Rating	U-Value Range
Two Panel	R-50 / LC-50	0.29 - 0.31
Four Panel	R-50 / LC-50	0.29 - 0.31
<b>SDL Depth (Max Profile Height)</b>		
Exterior	7/16"	
Interior	9/16"	



Quaker Window Products  
 504 U.S. Hwy 63 South  
 Freeburg, MO 65035  
 (800) 347-0438  
[www.quakerresidentialwindows.com](http://www.quakerresidentialwindows.com)

Discover More Here :

