


TimberVu Windows



Patented OptiCore® Technology

An engineering base that enhances structural, thermal and sound performance crafted to push the envelope of spatial home design.




Meticulous Construction

Tested to achieve high performance architectural rating, TimberVu Windows by Quaker offer an advanced thermal barrier system that allows for larger windows and greater views throughout your entire home.



Superior Thermal Performance

With a series of energy-enhanced glass packages, each window has been equipped for year-round maintenance-free versatility.



Rich and Classic Appearance

Combining a modern extruded aluminum exterior with a natural pine interior, TimberVu Windows offer the unique blending of advanced architectural design intertwined with a contemporary flair.

Warm Interiors With Superior Product Features

TimberVu Window Highlights, Performance and Operation

- Patented OptiCore® Technology Framing System
 - 4-1/8" Architectural Grade Aluminum Frame
 - 4-9/16" & 6-9/16" Jamb Extensions
 - Dual Euro-Groove Frame System
- Azo-Core Thermal Barrier System for Increased Energy Efficiency and Reduced Thermal Conductivity
- Multiple Glazing Package Options Compliment Region and Climate
- Structural Mull Availability Offers Wider and Taller Sizing Options
- Square (C600) and Bevel (C605) Stop Options for Enhanced Exterior Look
- Internal or Simulated Divided Lights (SDLs) Grids Available
- Pine Interior
- High-Performance 2604 and 2605 Powder Finishes
- Custom Color Matching and Heat Reflective Paint Options
- Easily Removable FlexScreen System

Series Options	
W600	Square
W605	Beveled

Operation	Window Sizing				
	Width		Height		Max. UI
	Min	Max	Min	Max	
Awning Push Out	18"	72"	22"	48"	132"
Awning Roto	24"	72"	24"	84"	132"
Casement Push Out	24"	48"	22"	72"	132"
Casement Roto	24"	48"	22"	96"	132"
Direct Set	15"	144"	15"	144"	216"

Window Performance (W600 / W605)						
Operation	Rating	Structural Load (P.S.F.)	Air Infiltration	Water (P.S.F.)	U-Value	SHGC
Direct Set	AW-PG90	90.22	0.01	12.11	0.14 - 0.28	0.24 - 0.36
Casement	AW-PG70	70.18	0.01	12.11	0.17 - 0.28	0.19 - 0.29
Casement Push-Out	Aw-100	70.18	0.01	12.11	0.17 - 0.28	0.19 - 0.29
Awning	AW-PG70	70.18	0.01	12.11	0.17 - 0.28	0.19 - 0.29

Interior & Exterior Color Options



* Heat Reflective Option Available.

Interior Prefinish Options



Quaker Window Products
 504 U.S. Hwy 63 South
 Freeburg, MO 65035
 (800) 347-0438
www.quakerresidentialwindows.com

Discover More Here:



RES-TV W 0925